

[bash](#), [howto](#), [commandlineediting](#), [keyboard](#), [shortcut](#)



## Bash - Command Line Editing

### Sources

- <https://ss64.com/bash/syntax-keyboard.html>
- <https://www.howtogeek.com/howto/ubuntu/keyboard-shortcuts-for-bash-command-shell-for-ubuntu-debian-suse-redhat-linux-etc/>

### Basic Shortcuts

Bash is the default command-line shell on most Linux distributions and included in macOS. On Windows you can install a Linux-based bash environment ([WSL](#), [Cygwin](#)).

The bash shell features a wide variety of keyboard shortcuts you can use. These will work in bash on any operating system. Some of them may not work if you're accessing bash remotely through an SSH or telnet session, depending on how you have your keys mapped.

| Shortcut | Command   |
|----------|---|
| CTRL+L   | Clear the screen.   |
| CTRL+W   | Delete the word starting at cursor.                           |
| CTRL+U   | Clear the line i.e. Delete the all words from command line.   |
| ↑, ↓     | Recall commands (see command history).                        |
| TAB      | Auto-complete files, directory, command names and much more.  |
| CTRL+R   | Search through previously used commands (see command history) |
| CTRL+C   | Cancel currently running commands.                            |
| CTRL+T   | Swap the last two characters before the cursor.               |
| ESC+T    | Swap the last two words before the cursor.                    |

### Bash Keyboard Shortcuts

#### TAB completion

**Tab completion** is a very useful bash feature. While typing a *file name*, *directory name*, or *command name*, press `TAB` and bash will automatically complete what you're typing, if possible. If not, bash will show you various possible matches and you can continue typing and pressing `TAB` to finish typing.

| Shortcut | Command   |
|----------|---|
| TAB      | Automatically complete the file, directory, or command you're typing. |

For example: if you have a file named *really\_long\_file\_name* in */home/user/* and it's the only file name starting with "r" in that directory, you can type */home/user/r*, press `TAB`, and bash will automatically fill in */home/user/really\_long\_file\_name* for you. If you have multiple files or directories starting with "r", bash will inform you of your possibilities. You can start typing one of them and press `TAB` to continue.

#### Moving the cursor

Use the following shortcuts to quickly move the cursor around the current line while typing a command.

| Shortcut     | Command  |
|--------------|--|
| Ctrl+A, POS1 | Go to the beginning of the line (Home)   |
| Ctrl+E, END  | Go to the End of the line (End)  |
| ALT+B        | Back (left) one word   |
| ALT+F        | Forward (right) one word   |
| Ctrl+F       | Forward one character  |
| Ctrl+B       | Backward one character   |
| Ctrl+Xx      | (double tap 'X' ) Move between the beginning of the line and the current position of the cursor. This allows you to press <code>Ctrl+Xx</code> to return to the start of the line, change something, and then press <code>Ctrl+Xx</code> to go back to your original cursor position. To use this shortcut, hold the <code>Ctrl</code> and tap <code>X</code> twice. |

## Editing

Use the following shortcuts to quickly delete characters, fix typos and undo your key presses. Bash also includes some basic cut-and-paste features and is able to convert characters to upper or lower case.

| Shortcut      | Command   |
|---------------|---|
| CTRL+L        | Clear the Screen, similar to the clear command  |
| ALT+BACKSPACE | Delete the Word before the cursor.  |
| CTRL+D        | Delete character under the cursor   |
| ALT+D         | Delete from actual cursor position to the end of word   |
| CTRL+H        | Delete character before the cursor (Backspace)  |
| CTRL+W        | Cut the Word before the cursor to the clipboard.  |
| CTRL+K        | Cut the Line after the cursor to the clipboard.   |
| CTRL+U        | Cut/delete the Line before the cursor to the clipboard.   |
| ALT+T         | Swap current word with previous   |
| CTRL+T        | Swap the last two characters before the cursor (typo).  |
| ESC+T         | Swap the last two words before the cursor.  |
| CTRL+Y        | Paste the last thing to be cut (yank)   |
| ALT+U         | Capitalize every character from the cursor to the end of the current word, converting the characters to upper case.   |
| ALT+L         | Uncapitalize every character from the cursor to the end of the current word, converting the characters to lower case. |
| ALT+C         | Capitalize the character under the cursor. Your cursor will move to the end of the current word.                      |
| ALT+R         | Cancel the changes and put back the line as it was in the history (revert).   |
| CTRL+_        | Undo  |

## Special keys: Tab, Backspace, Enter, Esc

Text Terminals send characters (bytes), not key strokes. Special keys such as **Tab**, **Backspace**, **Enter** and **Esc** are encoded as control characters. Control characters are not printable, they display in the terminal as ^ and are intended to have an effect on applications.

| Keys   | Control Character |
|--------|-------------------|
| Ctrl+I | TAB               |
| Ctrl+J | Newline           |
| Ctrl+M | ENTER             |
| Ctrl+[ | ESC               |

Many terminals will also send control characters for keys in the digit row:

| Shortcut | Result                  |
|----------|-------------------------|
| CTRL+2   | ^@                      |
| CTRL+3   | ^[ ESCAPE               |
| CTRL+4   | ^\                      |
| CTRL+5   | ^]                      |
| CTRL+6   | ^^                      |
| CTRL+7   | ^_ UNDO                 |
| CTRL+8   | ^? Backward-delete-char |

CTRL+V tells the terminal to not interpret the following character, so CTRL+V CTRL+I will display a **TAB** character, similarly CTRL+V ENTER will display the escape sequence for the Enter key: ^M.

## History

| Shortcut    | Command  |
|-------------|--|
| CTRL+R or ↑ | Recall the last command including the specified character(s). Searches the command history as you type. Equivalent to : vim ~/.bash_history. |
| CTRL+P or ↓ | Previous command in history (i.e. walk back through the command history)   |
| CTRL+N      | Next command in history (i.e. walk forward through the command history)  |
| CTRL+Shift  | Go back to the next most recent command. (beware to not execute it from a terminal because this will also launch its XOFF).                  |
| CTRL+O      | Execute the command found via Ctrl+R or Ctrl+S   |
| CTRL+G      | Escape from history searching mode   |
| !!          | Repeat last command  |
| !abc        | Run last command starting with abc   |

| Shortcut              | Command                                      |
|-----------------------|--|
| !abc:p                | Print last command starting with abc         |
| !\$                   | Last argument of previous command            |
| <b>ALT</b> + <b>.</b> | Last argument of previous command            |
| !*                    | All arguments of previous command            |
| ^abc^def              | Run previous command, replacing abc with def |

## Process control

Use the following shortcuts to manage running processes.

| Shortcut               | Command   |
|------------------------|---|
| <b>CTRL</b> + <b>C</b> | Interrupt (kill) the current foreground process running in in the terminal. This sends the <b>SIGINT signal</b> to the process, which is technically just a request—most processes will honor it, but some may ignore it. |
| <b>CTRL</b> + <b>D</b> | Close the bash shell. This sends an <b>EOF</b> (End-of-file) marker to bash, and bash exits when it receives this marker. This is similar to running the exit command.  |
| <b>CTRL</b> + <b>Z</b> | Suspend the current foreground process running in bash. This sends the <b>SIGTSTP signal</b> to the process. To return the process to the foreground later, use the <b>fg process_name</b> command.                       |

## Controlling the screen

The following shortcuts allow you to control what appears on the screen.

| Shortcut               | Command   |
|------------------------|---|
| <b>CTRL</b> + <b>L</b> | Clear the screen. This is similar to running the “clear” command.   |
| <b>CTRL</b> + <b>S</b> | Stop all output to the screen. This is particularly useful when running commands with a lot of long, verbose output, but you don’t want to stop the command itself with |
| <b>CTRL</b> + <b>Q</b> | Resume output to the screen after stopping it with <b>Ctrl</b> + <b>Shift</b> .   |

## Emacs mode vs Vi Mode

All the above assume that bash is running in the **default Emacs setting**, if you prefer this can be switched to **Vi shortcuts** instead.

Set **Vi Mode** in bash:

```
set -o vi
```

Set **Emacs Mode** in bash:

```
set -o emacs
```

“...emacs, which might be thought of as a thermonuclear word processor” ~ [Emacs vs. Vi Wiki](#)

## Related

- [fg](#) - Bring a command to the foreground.
- [vi editor](#) - [A one page reference to the vi editor.](#)
- [~/.bash\\_history](#) - Text file with command history.
- [Terminals Are Weird](#) - How and why of terminal keybindings.
- Equivalent [Windows Keyboard shortcuts](#)

From:  
<https://wiki.nanoscopic.de/> - **nanoscopic wiki**

Permanent link:  
<https://wiki.nanoscopic.de/doku.php/pages/howtos/bash/bash-command-line-editing?rev=1613048459>

Last update: **2021/02/11 13:00**



