

[howto](#), [dig](#), [diagnose](#), [dns](#), [rdns](#), [spf](#)

# How to Diagnose DNS and RDNS with DIG

## Sources:

- [IBM NS1 - Decoding DIG Output](#)
- [serverfault - How to determine which DNS server has the authority to set rDNS \(PTR records\)?](#)
- [linux.die.net - dig\(1\) - Linux man page](#)

## DIG Basic Usage

```
dig -t ANY @a.ns14.net nanoscopic.de
```

- dig: calling the command dig
- -t ANY: specifying the query type
- @a.ns14.net: specifying the DNS server to query
- nanoscopic.de: the name to query for

## Find Authoritative DNS Server

```
dig -t SOA nanoscopic.de
```

```
; <<>> DiG 9.18.26 <<>> -t SOA nanoscopic.de
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 22729
;; flags: qr rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1424
;; QUESTION SECTION:
;nanoscopic.de.                IN      SOA

;; ANSWER SECTION:
nanoscopic.de.                3600    IN      SOA      a.ns14.net. domains.wiretrip.de. 2024031401 43200 7200
1209600 3600

;; Query time: 26 msec
;; SERVER: 192.168.1.1#53(192.168.1.1) (UDP)
;; WHEN: Mon May 06 17:50:07 CEST 2024
;; MSG SIZE rcvd: 105
```

The authoritative DNS server for nanoscopic.de is a.ns14.net.

## Query the authoritative DNS server (or a specific DNS server) for current data

To get current DNS data, use @<HOSTNAME\_OF\_AUTHORITATIVE\_DNS\_SERVER>.

## IPv4

```
dig @a.ns14.net -t A nanoscopic.de
```

```
; <<>> DiG 9.18.26 <<>> @a.ns14.net -t A nanoscopic.de
; (2 servers found)
```

```
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 32234
;; flags: qr aa rd; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1
;; WARNING: recursion requested but not available

;; OPT PSEUDOSECTION:
;; EDNS: version: 0, flags::; udp: 1232
;; QUESTION SECTION:
;nanoscopic.de.                IN      A

;; ANSWER SECTION:
nanoscopic.de.                3600    IN      A      159.69.16.204

;; Query time: 16 msec
;; SERVER: 62.116.159.231#53(a.ns14.net) (UDP)
;; WHEN: Mon May 06 17:56:47 CEST 2024
;; MSG SIZE rcvd: 58
```

## IPv6

```
dig @a.ns14.net -t AAAA nanoscopic.de
```

```
; <<>> DiG 9.18.26 <<>> @a.ns14.net -t AAAA nanoscopic.de
; (2 servers found)
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 21488
;; flags: qr aa rd; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1
;; WARNING: recursion requested but not available

;; OPT PSEUDOSECTION:
;; EDNS: version: 0, flags::; udp: 1232
;; QUESTION SECTION:
;nanoscopic.de.                IN      AAAA

;; ANSWER SECTION:
nanoscopic.de.                3600    IN      AAAA   2a01:4f8:c0c:fa5c::1

;; Query time: 16 msec
;; SERVER: 62.116.159.231#53(a.ns14.net) (UDP)
;; WHEN: Mon May 06 17:58:31 CEST 2024
;; MSG SIZE rcvd: 70
```

## Determine the DNS Server holding a RDNS (PTR) Record

### How to interpret DIG output

~~DISCUSSION~~

From: <https://wiki.nanoscopic.de/> - nanoscopic wiki

Permanent link: <https://wiki.nanoscopic.de/doku.php/pages/howtos/diagnose/how-to-diagnose-dns-with-dig?rev=1715017103>

Last update: 2024/05/06 17:38

